



# TITANIUM GATEWAY

STOCK AND SALES COMPANY FOR TITANIUM AND SPECIAL ALLOYS

## Titanium Grade 2 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F67 / ISO 5832-2

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
2,00 mm	h 7	105,6	
3,00 mm	h 7	50,2	
5,00 mm	h 7	100,4	
6,00 mm	h 8	883,0	
8,00 mm	h 8	224,1	
10,00 mm	h 8	18,7	(300,0)
12,00 mm	h 8	292,0	
14,00 mm	h 8	194,1	
15,00 mm	h 8	142,5	
16,00 mm	h 9	292,7	
18,00 mm	h 9	213,7	(200,0)
20,00 mm	h 9	249,0	(700,0)
22,00 mm	h 9	175,6	
25,00 mm	h 9	28,8	(1400,0)
30,00 mm	h 9	852,0	(700,0)
35,00 mm	h 9	197,3	(500,0)
40,00 mm	-0/+0.100	0,0	(1500,0)
45,00 mm	-0/+0.100	278,0	(300,0)
50,00mm	-0/+0.100	918,6	
55,00 mm	-0/+0.100	1466,9	(200,0)
60,00 mm	-0/+0.120	1640,2	
65,00 mm	-0/+0.120	728,7	
70,00 mm	-0/+0.140	116,0	(500,0)
80,00 mm	-0/+0.140	335,2	
90,00 mm	-0/+0.200	439,9	
100,00 mm	-0/+0.500	584,6	
110,00 mm	-0/+0.500	133,4	(257,2)
120,00 mm	-0/+0.500	290,9	
130,00 mm	-0/+0.500	172,7	(360,0)
140,00 mm	-0/+0.500	427,3	
150,00 mm	-0/+0.500	308,6	
160,00 mm	-0/+0.500	388,4	
170,00 mm	-0/+0.500	635,6	
180,00 mm	-0/+0.500	381,2	
190,00 mm	-0/+0.500	210,0	



# TITANIUM GATEWAY

STOCK AND SALES COMPANY FOR TITANIUM AND SPECIAL ALLOYS

## Titanium Grade 2 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F67 / ISO 5832-2

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
200,00 mm	-0/+0.500	529,9	
225,00 mm	-0/+0.500	242,5	
250,00 mm	-0/+0.500	362,0	

## Titanium Grade 4 Round bar

Spec: ASTM B348 / ASME SB348 / ISO5832-2 / ASTM F67

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
100,00 mm	-0/+0.500	328,2	
130,00 mm	-0/+0.500	352,8	

## Titanium Grade 5 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F136 ELI / ISO 5832-3 / AMS 4928

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
2,00 mm	h 7	39,6	
3,00 mm	h 7	1,7	(150,0)
4,00 mm	h 7	109,6	
5,00 mm	h 7	169,7	
6,00 mm	h 8	173,1	(113,5)
8,00 mm	h 8	345,0	
10,00 mm	h 8	510,5	
12,00 mm	h 8	354,8	
14,00 mm	h 8	391,4	
15,00 mm	h 8	400,8	
16,00 mm	h 9	417,0	
18,00 mm	h 9	286,1	
20,00 mm	h 9	570,8	(600,0)
22,00 mm	h 9	390,9	
25,00 mm	h 9	502,1	(800,0)
30,00 mm	h 9	307,6	
35,00 mm	h 9	825,2	
36,00 mm	h 9	207,3	(200,0)
40,00 mm	-0/+0.100	437,3	(800,0)
45,00 mm	-0/+0.100	322,9	
50,00 mm	-0/+0.100	598,3	(400,0)
55,00 mm	-0/+0.100	205,2	



# TITANIUM GATEWAY

STOCK AND SALES COMPANY FOR TITANIUM AND SPECIAL ALLOYS

## Titanium Grade 5 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F136 ELI / ISO 5832-3 / AMS 4928

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
60,00 mm	-0/+0.120	30,4	(500,0)
65,00 mm	-0/+0.120	318,1	
70,00 mm	-0/+0.140	623,3	
75,00 mm	-0/+0.140	283,5	(400,0)
80,00 mm	-0/+0.140	292,4	(340,0)
90,00 mm	-0/+0.200	484,6	
100,00 mm	-0/+0.500	1959,8	
110,00 mm	-0/+0.500	233,6	(257,0)
120,00 mm	-0/+0.500	514,3	
130,00 mm	-0/+0.500	331,4	
140,00 mm	-0/+0.500	335,7	
150,00 mm	-0/+0.500	408,5	
160,00 mm	-0/+0.500	189,5	
170,00 mm	-0/+0.500	535,2	
180,00 mm	-0/+0.500	136,7	
190,00 mm	-0/+0.500	164,2	
200,00 mm	-0/+0.500	292,1	
225,00 mm	-0/+0.500	47,0	
230,00 mm	-0/+0.500	402,8	
250,00 mm	-0/+0.500	235,5	

## Titanium Grade 1 sheets

Spec: ASTM B265 GR1 edition 2015 / ASM SB 265 Gr1 edition 2015 DIN 17860 / NACE MR0175/ PED 2014/68/EU / AL 111 4890-63 rev. 13

Contidtion: cold rolled, annealed

Dimension	QTY (kg)	Incoming
0,6 x 1000 x 2500	932,0	
0,8x 1000 x 2500	173,6	(558,0)
1,0 x 1250 x 3000	2742,3	
1,5 x 1250 x 3000	729,1	
2,0 x 1250 x 3000	266,8	(1002,0)
2,5 x 1250 x 3000	212,8	
3,0 x 1250 x 3000	864,7	
4,0 x 1000 x 2000	399,5	
5,0 x 1000 x 2000	333,5	
6,0 x 1000 x 2000	101,5	



# TITANIUM GATEWAY

STOCK AND SALES COMPANY FOR TITANIUM AND SPECIAL ALLOYS

## Titanium Grade 2 sheets

Spec: ASTM B265 GR2 -2015 / ASME SB 265 GR2 -2015

PED 2014/68/EU/ NACE MR0175

Condition: cold rolled, annealed, polished/pickled

Dimension	QTY (kg)	Incoming
1,0x1000x2000	493,7	
1,5x1000x2000	358,9	
15,0x2000x3000	1730,0	
2,0x1000x2000	1107,6	(990,0)
3,0x1000x2000	411,2	(405,0)
4,0x1000x2000	222,0	
5,0x1000x2000	236,9	

## Titanium Grade 5 sheets

Spec: ASTM B265/ASME SB265

Condition: cold rolled, annealed, grinded surface

Dimension	QTY (kg)	Incoming
1 x 1000 x 2000	61,6	
1 x 1000 x 2000	131,5	
2 x 1000 x 2000	341,6	
3 x 1000 x 2000	481,6	
3 x 1250 x 2500	206,0	
4 x 1000 x 2000	107,1	
5 x 1000 x 2000	92,6	

## Titanium Grade 2 Profiles

Spec: ASTM B265

Condition: hot rolled, annealed, straight, black and sandblasting surface

Dimension	QTY (kg)	Incoming
9,5 x 9,5	107,4	
12,7 x 12,7	192,0	
19,05 x 19,05	285,0	
25,4 x 6,35	72,2	
25,4 x 12,7	233,6	
25,4 x 25,4	573,8	